HIGH CAPACITY MANURE GRAB


AGRICULTURAL HANDLING Solutions


ADVANTAGES


- Massive and efficient attachment.
- Excellent visibility thanks to innovative design.
- The best solution for manure handling.
- Improved design allows working flush with walls.
- Versatile attachment that enables occasional square bale handling.

TECHNICAL CHARACTERISTICS

- Large capacity 2000 L.
- Grapple "open/close" stop plates ensure long life for hydraulic cylinders.
- Bolt-on teeth and tines for easy maintenance.
- High quality wear resistant and high yield steels used extensively.
- Teeth: Ø 45 mm, 939 mm.
- Tines: Ø 45 mm, 1100 mm.







	Capacity (L)	A (mm)	B (mm)	C (mm)	D (mm)	E (mm)	Teeth	Tines	Weight (kg)
FMG 2100/1800	1800	2095	1223	1352	-	-	4	10	470
FMG 2450/2000	2000	2435	1225	1411	1932	134	5	12	686

COMPATIBILITY*

	FMG 2100/1800	FMG 2450/2000
Part Number	52000082	790534
MLT 629	X	
MLT 634		X
MLT 735		Х
MLT 741		X
MLT 840		X
MLT 1040		X

This Attachment has been approved for the machines listed above. A load chart Machine/Attachment has been created accordingly.



